

모델 및 규격

주거용 건물

상업용 건물

산업/공장 시설물

Vulcan 3000

Vulcan 5000

Vulcan S10

Vulcan S25

Vulcan S50

Vulcan S100

Vulcan S150

Vulcan S250

Vulcan S350

Vulcan S500



파이프 굵기	1 ¹ / ₂ " (~ 38 mm)	2" (~ 50 mm)	3" (~ 76 mm)	4" (~ 100 mm)	5" (~ 125 mm)	6" (~ 150 mm)	8" (~ 200 mm)	10" (~ 250 mm)	14" (~ 350 mm)	20" (~ 500 mm)
최대 용량	3000 l/h	8000 l/h	15 m ³ /h	30 m ³ /h	70 m ³ /h	120 m ³ /h	180 m ³ /h	350 m ³ /h	500 m ³ /h	800 m ³ /h
전원	24 Volt	24 Volt	24 Volt	24 Volt	24 Volt	24 Volt	24 Volt	24 Volt	24 Volt	24 Volt
소비전력	2,0 Watt	2,0 Watt	2,25 Watt	2,25 Watt	2,25 Watt	2,5 Watt	2,5 Watt	2,75 Watt	2,75 Watt	3,25 Watt
임펄스 밴드	2 x 1 m	2 x 2 m	2 x 3 m	4 x 3 m	4 x 4 m	6 x 4 m	6 x 8 m	8 x 10 m	8 x 20 m	10 x 30 m
밴드 너비	10 mm	10 mm	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm
메인보드 사이즈(mm)	125/80/30	150/90/30	190/120/40	200/130/40	200/130/40	230/150/40	230/150/40	280/200/50	280/200/50	310/220/50
주파수 프리퀀시	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz
설치공간	~ 250 mm	~ 350 mm	~ 500 mm	~ 800 mm	~ 900 mm	~ 1200 mm	~ 1800 mm	~ 2500 mm	~ 3400 mm	~ 4500 mm
프로그램	1	1	3	5	5	10	10	10	10	10

X-Pro Line (X-프로라인)



Vulcan X-Pro 1



Vulcan X-Pro 2



파이프 굵기	30" (~ 750 mm)	40" (~ 1000 mm)
전원	24 Volt	24 Volt
소비전력	3.75 Watt	3.75 Watt
임펄스 밴드	12 x 25 m	12 x 50 m
밴드 너비	40 mm	40 mm
메인보드 사이즈	340/240/50 mm	340/240/50 mm
주파수 프리퀀시	3-32 kHz	3-32 kHz
설치공간	~ 5600 mm	~ 8200 mm
프로그램	10	10